



3	Shell	1	Brass	T=0.40mm	Tin or Nickel Plated
2	Contact	6	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO.:		MATERIAL:	
MODEL NO.:		FINSH:	
UNIT: mm	SIZE: A4	COLOR:	

TOLERANCE UNSPECIFIED		DR: 段林麗 06/03/02		DWG NO: S/A-349		REV: A0	
X	±0.3	CHK: Song	06/03/02	SCALE: 3:1		SHEET: 1 of 1	
.XX	±0.20	APP: Kent	06/03/02	REV: A0			
.XXX	±0.100						
ANG.	±1°						

- Note:
1. Material:
- 1.1 Insulator: P.B.T UL 94-V0 rated.
 - 1.2 Contact: Brass, t=0.25mm.
 - 1.3 Shell: Brass, t=0.40mm.
2. Specification:
- 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
 - 2.3 Contact resistance: 30 mΩ Max.
 - 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
 - 2.5 Total mating force: 4.5 Kgf Max.
 - 2.6 Total unmating force: 1.5 Kgf Min.
 - 2.7 Temperature range: -55°C~+105°C
3. Finishes:
- 3.1 Contacts: Gold flashed 1u", 3u", 5u", 10U", 15u", 30u".
 - 3.2 Shell: Tin or Nickel Plated.

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD